

180kW Free Standing DC Fast Charger



ELECTRICAL – DC OUTPUT				
NUMBER OF PORTS	Two			
POWER	180 kW Ma			
CURRENT	200A Max @ (150Vdc ~ 900Vdc); 190A Max @ 950Vdc	300A Max @ (150Vdc ~ 600Vdc); 190A Max @ 950Vdc		
VOLTAGE	150 ~ 950 VDC			
CHARGING CONNECTOR	CCS1			
CHARGING INTERFACE	DIN 70121, ISO15118			
ELECTRICAL – AC INPUT				
POWER	196 kVA Max			
CURRENT	3-phase: 233A Max			
VOLTAGE	3-phase: 277Y/480Y VAC			
FREQUENCY	50/60 Hz			
POWER FACTOR	> 0.99			
SAFETY				
INPUT PROTECTION	Over/under voltage, over current, over power, over temperature and surge protection			
OUTPUT PROTECTION	Over/under voltage, over-current, over temperature and short-circuit protection			
INTERNAL PROTECTION	Over temperature detection, AC contactor detection, DC contactor detection, Fuse detection			
NETWORK				
DATA COMMUNICATION	Cellular 4G LTE, Wi-Fi, Ethernet	Cellular 4G LTE	Cellular 4G LTE, Wi-Fi, Ethernet	Cellular 4G LTE
CHARGING INFRASTRUCTURE COMMUNICATION	OCPP Compliant			
REMOTE MANAGEMENT	Over-the-Air (OTA) software update enabled			

*The product image shown is for illustration purposes only and may not be an exact representation of the product.

180kW Free Standing DC Fast Charger



USER INTERACTION				
DISPLAY	7" LCD			
AUTHENTICATION AND PAYMENT	RFID Reader: ISO14443 Type A & B, MiFare, Felica; ISO15693	Credit Card Reader: Apple Pay, Google Pay; Contactless Magnetic, EMV Credit Card	RFID Reader: ISO14443 Type A & B, MiFare, Felica; ISO15693	Credit Card Reader: Apple Pay, Google Pay; Contactless Magnetic, EMV Credit Card
ENVIRONMENTAL				
ENCLOSURE	NEMA 3R, outdoor rated			
OPERATING HUMIDITY	Up to 95% non-condensing			
OPERATING TEMPERATURE	-30 °C~50 °C (-22°F ~ +122°F)			
OPERATING ALTITUDE	≤ 2000m (6562ft)			
COOLING METHOD	Forced air			
MECHANICAL				
DIMENSIONS	(75" H x 32" W x 26" D) ±1%			
APPROXIMATE WEIGHTS	< 500kg (1102lbs) ±1% with two charging cable			
MOUNTING OPTION	Stand alone			
CABLE LENGTH	15 ft standard, 23 ft optional			
CABLE ORGANIZER	Optional			
MECHANICAL				
SAFETY	UL 2202, UL 2231-1, UL 2231-2			
EMI	FCC Part 15 Class A			
ENERGY EFFICIENCY	Energy Star Certified			
ACCESSIBILITY	ADA compliant			

*The product image shown is for illustration purposes only and may not be an exact representation of the product.