

Series 6 EV Charging Station



ELECTRICAL SPECIFICATION – AC OUTPUT	
Number of Ports	One
Current	Configurable up to 30A Max
Power	7.2 kW (@240VAC) or 6.24kW (@208VAC) Max
Energy Metering Accuracy	+/- 1%
Charging Connector	SAE J1772
ELECTRICAL SPECIFICATION – AC INPUT	
Input Connector	Hardwired
Voltage	208 or 240 VAC
Service Panel Breaker	Two-pole common trip 40A breaker, dedicated circuit
Power Connection	Line 1, Line 2 and GND (no neutral)
Standby Power	4.11 W Typical
SAFETY SPECIFICATION	
Ground Fault Circuit Interrupt	20mA CCID with auto retry (every 15 seconds)
Automatic Plug-Out Detection	Power terminated per SAE J1772 spec
Surge Protection	6kV @3,000A
NETWORK SPECIFICATION	
Data Communication	Cellular 4G LTE
Charging Infrastructure Communication	OCPP 1.6 compliant
Remote Management	Remote access, diagnostics, Over-the-Air (OTA) software update enabled
Load Management	Smart, dynamic allocation and distribution of power to EVSEs

Series 6 EV Charging Station



USER INTERACTION SPECIFICATION	
Charging Status Indicator	High visibility, multi-color LED visual status indication
Display	LCD Screen - 2 lines, 16 characters per line
Authentication	RFID: ISO14443 Type A & B, MiFare, Felica, ISO15693
ENVIRONMENTAL SPECIFICATION	
Enclosure	Aluminum, NEMA 3R certified
Operating Humidity	Up to 95% non-condensing
Operating Temperature	-30 degree C to +50 degree C ambient
Operating Altitude	≤6560 ft
MECHANICAL SPECIFICATION	
Dimensions	Charging Head: 25" H x 6" W x 6" D
Approximate Weights	Charging Head: 15.5 lbs. Pedestal: 9 lbs.
Mounting Option	Wall or Pedestal mount
Cable Length	18 ft standard, 25 ft optional
Cable Organizer	Optional
REGULATION	
Safety	UL 2594 / CSA C22.2 No. 280-16, UL 2231-1 / CSA C22.2 No. 281.1-12, UL 2231-2 / CSA C22.2 No. 281.2-12 certified
EMI	FCC Part 15 Class A compliant
Energy Efficiency	Energy Star certified
Compliance	California Type Evaluation Program (CTEP) certified, Buy American ACT (BAA) compliant
Accessibility	ADA Compliant